Part No 41035

MINI DISPLAYPORT 1.2 TO HDMI, DVI & VGA CONVERTER

CONNECTS A MINI DISPLAYPORT SOURCE TO AN HDMI, DVI OR VGA DISPLAY



DESCRIPTION

- Converts a DisplayPort signal to HDMI, DVI or VGA
- Supports HDMI resolutions up to 4K@30Hz, VGA up to Full HD and DVI up to and above Full HD
- Easily connect with a single legacy or modern display at any one time
- Compact, portable design
- 2 year warranty

The Lindy Mini DisplayPort to HDMI, DVI and VGA Converter allows users to connect either a HDMI, DVI or VGA screen to a Mini Displayport source. Supporting 4K resolutions up to 3840x2160@30Hz on HDMI displays, content can be viewed with superior clarity and stunning accuracy. DVI monitors are supported with a maximum resolution of 1920x1200@60Hz, VGA monitors and projectors up to 1920x1080@60Hz.

With its lightweight, low profile design, this converter easily fits into a notebook bag and simply expands available connectivity options, so users can connect to the most commonly used digital and analogue video equipment, without having to carry multiple adapters - ideal for BYOD applications.

RELATED PRODUCTS

N/A

MINI DISPLAYPORT 1.2 TO HDMI, DVI & VGA CONVERTER

SPECIFICATIONS

AV Interface	DisplayPort to HDMI, VGA, DVI
Interface Standard	DisplayPort 1.2, HDMI 1.4, VGA,
Supported Bandwidth	21.6Gbps
Maximum Input Resolution	3840x2160@30Hz
Maximum Output Resolution	HDMI: 3840x2160@30Hz DVI: 1920x1200@60Hz VGA: 1920x1200@60Hz
Chipset	Paradetech PS8339
HDCP Support	HDCP 1.4
Supported Audio	Pass-through for HDMI
Separate Audio Ports	-
Special Features	-

CONNECTORS

Input	Mini DisplayPort Male
Output	HDMI Type A Female VGA Female DVI-D Female

MISCELLANEOUS

Packaging Type	Polybag
Packaging Dimension	160x160x20mm (6.3x6.3x0.79in)
Gross Weight	0.06kg (0.13lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	60x60x16,4mm (2.36x2.36x0.65in) / Housing 10.9x24.5y8mm (0.43x0.96x0.31in)
Cable Length	200mm (7.87in)
Housing Material	ABS
Jacket Material	PVC
Jacket Diameter	5mm (0.2in)
Minimum Bend Radius	50mm (1.97in)
Net Weight	0.053kg (0.12lb)
Operating Temperature	0°C - 70°C (32°F - 158°F)
Storage Temperature	-20°C - 70°C (-4°F - 158°F)
Humidity	10 - 85% RH (non-condensing)
Colour	White

PURCHASING INFORMATION

No.	41035
EAN	4002888410359

PACKAGING CONTENTS

Mini DisplayPort 1.2 to HDMI 1.4, DVI & VGA Converter