Part no:

36467 - 69

4K60 HDMI Cable, Black Line (7.5m, 10m, 15m)





| DESCRIPTION

- Entry Level Standard HDMI 2.0 cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@30hz 4:4:4 8bit
- Robust PVC housing, Nickel Connectors, 24k gold plated contacts
- Triple shielded cable, corrosion resistant copper coated steel 28AWG conductors
- 10 year warranty

From the lines cable connectivity concept developed by Lindy, Black Line 4K60 HDMI cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line 4K60 HDMI cables feature triple shielded construction with 28AWG copper coated steel conductors for premium performance and corrosion resistance. Nickel connectors and gold flashed contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@30Hz 4:4:4 8bit are supported. Black Line 4K60HDMI cables are also capable of transmitting 32 channel audio and Dolby True HD.

The HDMI 2.0 specification is supported for 10.2Gbps bandwidth capacity in cable lengths up to 15m.

Black Line 4K60 HDMI cables are available in lengths from 7.5m to 15m

Connectors

- Connector A: HDMI Type A Male
- Connector B: HDMI Type A Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold Flash
- Dimensions (approx.) WxDxH: 19x34.1x10.6mm (0.75x1.34x0.42in)

Cable Construction

- Standard: Standard Speed HDMI with Ethernet
- Colour: Black
- Type: Round
- Jacket Diameter: 7mm (0.27in)
- Jacket Material: PVC
- Conductor Material: Copper Coated Steel
- Conductor Gauge: 28AWG
- Shielding: Aluminium Foil

Specifications

- Supported Bandwidth: 10.2Gbps
- Maximum Resolution: 4096x2160@30Hz 4:4:4 8bit
- Nominal Attenuation: 300kHz-825MHz <5dB, 825MHz-2.475GHz <5dB, 2.475GHz-4.125GHz <12dB, 4.125GHz-5.1GHz <20dB
- Minimum Bend Radius: 70mm (2.75in)
- Operating Temperature: -10°C - 80°C (14°F - 176°F)
- Storage Temperature: -10°C - 80°C (14°F - 176°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL

Available Lengths

- 36467 - 7.5m (24.60ft)
- 36468 - 10m (32.80ft)
- 36469 - 15m (49.21ft)